




SPECIFICATIONS:

Working Load Limit (WLL) = 10,000 lbs in Any Direction (Assy Only, See Warnings Page)

General Proof Load Tested to 125% (Individual Load Testing Available for Additional Fee)

Device is Designed to 3:1 based on yield strength per ASME BTH-1.

Swivel Hoist Ring is designed to 5:1 on ultimate strength and load tested to 2:1 (Meets ASME B30.26)

Device is classified as an ASME BTH-1 Design Catagory B, Service Class 0 Lifter

Dimensions: Approximately 18 inches Dia. x 10 inches tall

Max/Min Anchor Bolt Circle: 7-1/2 inches to 15 inches

Conduit Circle: 5 inch Diameter

Max Conduit Height: 5-3/8 inches

Anchor Bolt Slot Width: 1-1/2 inches

Assy Wt: Approximately 75 lbs

TRINITY TECHNICAL SOLUTIONS INC.
ALL INFORMATION GIVEN HEREIN IS PROPRIETARY. This document contains proprietary information of Trinity Technical Solutions Inc. This specification is intended solely for the information and use of parties operating and maintaining the equipment described herein. Such proprietary information may not be used, reproduced, or disclosed to any other parties for any other purpose without the expressed written permission of Trinity Technical Solutions Inc.

Web Site: www.riggingpickpoints.com
Email: trinity@riggingpickpoints.com
Phone: 208-497-4214

**POLE BASE LIFTER
MODEL 1 (PART NO. 01-09)
BASE DIMENSIONS**